

TEP



aquaviva®



TEP

ohrev parafínu a rašeliny
paraffin and peat pack warmer
огреватели парафина и торфа



Pracovná teplota rašelinových nosičov 40 - 45 °C
Pracovná teplota parafínu 56 - 58 °C
Sterilizačná teplota parafínu +- 80 °C
Rozsah regulácie teploty 0 - 90 °C
Typ ochrany pred úrazom el. prúdom trieda I.



Peat packs operating temperature 40 - 45 °C
Paraffin operating temperature 56 - 58 °C
Paraffin sterilizing temperature +- 80 °C
Temperature adjustment range 0 - 90 °C
Protection against electrical accident Class I



Рабочая температура торфяных теплоносителей 40 - 45 °C
Рабочая температура парафина 56 - 58 °C
Стерилизационная темп. парафина +- 80 °C
Диапазон регулировки температуры 0 - 90 °C
Тип защиты от поражения эл. током класс I



TEP BM 1115	330 x 540 x 220 mm	230V / 50Hz	1500 W
TEP BMV 1115	330 x 540 x 220 mm	230V / 50Hz	1500 W
TEP Plus BM 2115	660 x 540 x 220 mm	230V / 50Hz	2 x 1500 W
TEP PLUS BMV 2115	660 x 540 x 220 mm	230V / 50Hz	2 x 1500 W
TEP BM 1120	390 x 600 x 300 mm	230V / 50Hz	1500 W
TEP BMV 1120	390 x 600 x 300 mm	230V / 50Hz	1500 W
TEP PLUS BMV 2120	770 x 600 x 300 mm	230V / 50Hz	3000 W


CHIRANA PROGRESS

Chirana Progress, s.r.o.
Vrbovská cesta 17
921 01 Piešťany, Slovakia
tel.: +421 33 79 56 211
e-mail: chirana@chirana-progress.sk
www.chirana-progress.sk

dealer